

MT150 > Z-LUG RUBBER TRACK

The MT150 boasts its specialty in wet surfaces, encompassing a Z-Lug, self-cleaning stepped tread pattern for excellent traction while maintaining maximum cut and wear resistance. Featuring a heavy-duty carcass for stability and minimum sliding design.

- ▶ All around excellent traction, excelling in wet surfaces
- ▶ Heavy-duty carcass provides stability
- ▶ Stepped tread pattern for improved cleanout
- ▶ Cut and tear-resistant compound
- ▶ Increased net to gross for improved tread life
- ▶ Available in narrow and wide widths to best suit the working environment



TECHNICAL SPECIFICATIONS & APPLICATIONS



NAVISION NUMBER	MAXAM SIZE	WIDTH	PITCH	NUMBER OF LINKS	TREAD DEPTH	OVERALL CARCASS THICKNESS (MM)	WEIGHT		CARCASS (MM)	IGB (MM)	OGB (MM)	IGH (MM)	OGH (MM)	ROLLER TYPE
							KG	LBS						
V415000	320X86X49	320	86	49	24	73	151	332	49	48	95	48	36	RTO-2, RTO-4
V415001	320X86X50	320	86	50	24	73	152	334	49	48	95	48	36	RTO-2, RTO-4
V415002	320X86X52	320	86	52	24	73	160	352	49	48	95	48	36	RTO-2, RTO-4
V415003	320X86X53	320	86	53	24	73	163	359	49	48	95	48	36	RTO-2, RTO-4
V415004	320X86X55	320	86	55	24	73	169	372	49	48	95	48	36	RTO-2, RTO-4
V415005	400x86x49	400	86	49	26	75	180	397	49	48	95	48	36	RTO-2, RTO-4
V415012	400x86x50	400	86	50	26	75	186	410	49	48	95	48	36	RTO-2, RTO-4
V415006	400x86x52	400	86	52	26	75	196	432	49	48	95	48	36	RTO-2, RTO-4
V415013	400x86x53	400	86	53	26	75	197	434	49	48	95	48	36	RTO-2, RTO-4
V415014	400x86x55	400	86	55	26	75	204	450	49	48	95	48	36	RTO-2, RTO-4
V415007	400x86x56	400	86	56	26	75	206	453	49	48	95	48	36	RTO-2, RTO-4
V415015	450x86x52	450	86	52	26	75	210	463	49	48	95	48	36	RTO-2, RTO-4
V415016	450x86x53	450	86	53	26	75	214	472	49	48	95	48	36	RTO-2, RTO-4
V415017	450x86x55	450	86	55	26	75	222	489	49	48	95	48	36	RTO-2, RTO-4
V415008	450x86x56	450	86	56	26	75	226	498	49	48	95	48	36	RTO-2, RTO-4
V415009	450x86x58	450	86	58	26	75	230	507	49	48	95	48	36	RTO-2, RTO-4
V415018	450x86x60	450	86	60	26	75	242	533	49	48	95	48	36	RTO-2, RTO-4

