

MAXAM AGRIXTRA XL

MS951R - R1W RADIAL DRIVE TIRE VF/SERIES

Large volume R1W tires for high horsepower tractor applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
951120	600/65R28	154D	TL	DW20B	W18L, DW18L	24.1	611	58.7	1491	24.8	629	175.5	4458	42 700	64 51	346 157	124.6 472	19 x 2	297 1915
V951528	VF600/65R28	159D	TL	DW20B	DW21B	23.3	593	58.3	1482	24.6	623.8	176.4	4480	42 700	64 51	355 161	99.6 377	19 x 2	487 3142
V951331	600/70R28	161D	TL	DW20B		23.8	605	61.2	1555	27.7	705	183.5	4660	42 725	68 54	392 178	127.2 482	19 x 2	382 2463
V951529	VF600/60R30	158D	TL	DW20B	DW21B	23.1	586	58.2	1478	24.7	627.8	176.5	4482	42 700	64 51	333 151	93.3 353	20 x 2	461 2975
V951134	600/70R30	158D	TL	DW20B	W18L, DW18L	24.1	611	63.1	1602	27.9	709	188.6	4790	43 750	71 56	410 186	568 451	20 x 2	336 2170
V951332	VF600/70R30	165D	TL	DW21B	DW20B	24.8	630	63	1600	26.5	674	188.3	4784	43 750	71 56	414 188	123.4 467	20 x 2	527 3399
V951330	650/65R34	161D	TL	DW20B	DW23B	25.6	650	67.3	1710	29.5	750	197	5000	44 775	73 58	487 221	144 545	20 x 2	433 2795
V951530	VF650/65R34	167D	TL	DW23B	DW21B	26.3	667	66.4	1687	29.5	750	198.6	5044	44 825	73 58	503 228	139.5 528	20 x 2	545 3518
V951135	650/85R38	173D	TL	DW23B	DW20B	26.6	676	81.5	2071	36.0	914	243.8	6192	48 975	78 62	767 348	216 818	20 x 2	514 3319
V951123	710/70R38	171D	TL	DW23B		28.2	716	77.1	1959	34.3	870	230.6	5857	47 925	78 62	690 313	211.2 800	20 x 2	487 3140
V951136	800/70R38	178D	TL	DW25B		31.4	798	81.2	2085	36.2	919	245.5	6234	48 975	78 62	908 412	283 1072	21 x 2	594 3830

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

Continued



Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951125	710/70R42	173D	TL	DW23B		28.2	716	81.2	2061	36.3	921	242.6	6162	48 975	78 62	754 342	227.3 861	21 x 2	514 3319
V951227	710/75R42	175D	TL	DW23B	DW25B	28.2	716	84	2133	37.4	949	251.1	6378	49 1025	78 62	785 356	252.6 957	22 x 2	546 3523
V951501	650/75R38	169D	TL	DW20B		25.4	645	76.4	1941	34.7	880	230	5850	47 925	76 60	588 267	184.9 700	20 x 2	486 3134

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

VF/SERIES

Item Number	Size	LI / SS	Type	Rim (Rec.)	Rim (Alter.)	S.W.		O.D.		S.L.R.		R.C.		R.C.I. S.R.I.	Tread Depth 32nds mm	Weight lbs kg	75% of Int. Vol. gal l	# of Lugs	Gross Flat Plate sq in sq cm
						in	mm	in	mm	in	mm	in	mm						
V951332	VF600/70R30	165D	TL	DW21B	DW20B, DW18L, W18L	23.6	600	63	1600	27.4	695	188.3	4783	43 750	72 57	408 185	123.6 468	20 x 2	387 2497
V951530	VF650/65R34	167D	TL	DW23B	DW21B	25.6	650	67.3	1710	29.5	750	197	5000	44 775	73 58	487 221	144 545	20 x 2	433 2795
V951229	VF710/70R42	179D	TL	DW25B	DW23B	28.7	730	81.9	2080	35.3	896	248.8	6106	48 975	79 63	732 332	229 867	21 x 2	591 3813
V951536	VF710/75R42	181D	TL	DW23B	DW24B	28.4	720	83.3	2115	36.1	917	248.8	6320	49 1025	79 63	783 355	249.6 945	21 x 2	801 5165
V951528	VF600/65R28	159D	TL	DW21B	DW20B	23.5	597	58.7	1491	24.6	624	176.4	4480	42 700	64 51	356 162	99.6 377	19 x 2	487 3142
V951534	VF650/85R42	180D	TL	DW23B	DW20B, DW21B	25.3	642	85.6	2173	37.2	944	256.6	6517	49 1025	78 62	805 366	235.9 893	21 x 2	787 5076
V951532	VF710/60R38	171D	TL	DW25B	DW24B, DW27B	27.9	708	71.5	1817	30.6	776	209.1	5310	45 875	73 58	554 252	170.9 647	20 x 2	683 4408
V951529	VF600/60R30	158D	TL	DW20B	DW21B	23.5	597	58.3	1482	24.7	628	176.5	4482	42 700	64 51	332 151	93.3 353	20 x 2	461 2975
V951535	VF710/60R42	173D	TL	DW25B	DW24B, DW27B	27.9	708	75.6	1919	33	839	229.3	5825	47 925	74 59	605 275	183.9 696	21 x 2	676 4362
V951507	VF710/65R46	183D	TL	DW25B		28.1	715	82.5	2095	36.9	938	245	6223	48 1000	76 60	743 337	216.6 820	22 x 2	691 4456
V951546	VF900/60R42	189D	TL	DW30B		35.2	894	84.5	2141	36.4	924	255.7	6495	48 1025	81 64	1033 469	312.7 1184	21 x 2	914 5898

MAXAM AGRIXTRA XL

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Large volume R1W tires for high horsepower tractor applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering

AGRIXTRA XL LOAD AND INFLATION

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
600/65R28	154D	5/10 LT	5470/2480	6195/2810	6935/3145	7660/3475	8390/3805	9120/4135	9625/4365	10120/4590	10615/4815	11125/5045	12405/5625
		40/65		5150/2335	5700/2585	6240/2830	6780/3075	7155/3245	7530/3415	7895/3580	8270/3750		
VF600/65R28	159D	5/10 LT	7380/3350	8860/4020	9900/4490	11080/5030	12190/5530	12920/5860	14030/6370				
		40/65		7390/3350	8270/3750	9100/4125	9645/4375						
600/70R28	161D	5/10 LT	7060/3200	8030/3640	8950/4060	9810/4450	10430/4730	10950/4970	11500/5215	12040/5460	12390/5620	12730/5775	14270/6475
		40/65		6390/2900	7000/3175	7450/3380	7830/3550	8210/3725	8600/3900	8840/4010	9090/4125	10200/4625	
VF600/65R30	158D	5/10 LT	7610/3450	9090/4120	10200/4620	11440/5190	12530/5700	13670/6200					
		40/65		7610/3450	8540/3875	9350/4250							
600/70R30	158D	5/10 LT	6315/2865	7155/3245	8005/3630	8840/4010	9690/4395	10530/4775	11045/5010	11565/5245	12085/5480	12600/5715	14055/6375
		40/65		5955/2700	6570/2980	7200/3265	7830/3550	8215/3725	8600/3900	8985/4075	9370/4250		
VF600/70R30	165D	5/10 LT	8560/3890	9900/4490	11440/5190	12920/5860	13670/6200	15280/6900	16550/7500				
		40/65		8540/3875	9645/4375	10200/4625	11400/5150						
650/65R34	161D	5/10 LT	7826/3551	9112/4121	10519/4757	11792/5360	12931/5863	13668/6198					
		40/65	5840/2650	6800/3075	7850/3550	8800/4000	9650/4375	10200/4625					
VF650/65R34	167D	5/10 LT	9090/4120	10790/4890	12180/5530	14030/6370	14770/6700	16080/7300	17730/8040				
		40/65		9090/4125	10470/4750	11020/5000	12000/5450						
650/85R38	173D	5/10 LT	9700/4400	10990/4985	12280/5570	13570/6155	14875/6745	16165/7330	16945/7685	17715/8035	18500/8390	19285/8745	21500/9750
		40/65		9130/4140	10100/4580	11060/5015	12015/5450	12600/5715	13175/5975	13760/6240	14335/6500		

AGRIXTRA XL LOAD AND INFLATION

Continued

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)										
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	26 psi	29 psi	32 psi	35 psi	41 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	1.8 bar	2 bar	2.2 bar	2.4 bar	2.8 bar
710/70R38	171D	5/10 LT	9425/4275	10685/4845	11950/5420	13210/5990	14465/6560	15720/7130	16350/7415	16980/7700	17605/7985	18235/8270	20340/9225
		40/65		8885/4030	9810/4450	10750/4875	11685/5300	12160/5515	12625/5725	13100/5940	13560/6150		
800/70R38	178D	5/10 LT	11565/5245	13110/5945	14650/6645	16195/7345	17740/8045	19285/8745	20020/9080	20760/9415	21500/9750	22250/10090	24805/11250
		40/65		10895/4940	12040/5460	13185/5980	14335/6500	14885/6750	15435/7000	15985/7250	16540/7500		
710/70R42	173D	5/10 LT	9965/4520	11290/5120	12625/5725	13945/6325	15280/6930	16605/7530	17275/7835	17940/8135	18610/8440	19285/8745	21500/9750
		40/65		9380/4255	10375/4705	11355/5150	12350/5600	12845/5825	13340/6050	13835/6275	14335/6500		
710/75R42	175D	5/10 LT	10670/4840	12105/5490	13530/6135	14950/6780	16370/7425	17795/8070	18465/8375	19130/8675	19800/8980	20460/9280	22820/10350
		40/65		10055/4560	11115/5040	12170/5520	13230/6000	13725/6225	14220/6450	14720/6675	15215/6900		
650/75R38	169D	5/10 LT	8665/3930	9610/4360	10350/4695	11410/5175	12535/5685	13680/6205	16500/7485	17130/7770	0/	19180/8700	
		5/10 HT	6910/3135	7935/3600	9115/4135	10295/4670	11475/5205	12655/5740	13680/6205	14705/6670	0/	0/	
		15/25	7120/3230	8180/3710	9390/4260	10605/4810	11815/5360	13040/5915	14100/6395	15155/6875	0/	0/	
		20/30	6910/3135	7935/3600	9115/4135	10295/4670	11475/5205	12655/5740	13680/6205	14705/6670	0/	0/	
		25/40	0/	7550/3425	8675/3935	9800/4445	10925/4955	12050/5465	13030/5910	13890/6300	0/	0/	
		30/50	0/	7240/3285	8320/3775	9405/4265	10470/4750	11550/5240	12490/5665	13425/6090	0/	0/	
		40/65	0/	0/	7925/3595	8950/4060	9975/4525	11000/4990	11895/5395	12785/5800	0/	0/	

*LT = Low Torque

MAXAM AGRIXTRA XL

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Large volume R1W tires for high horsepower tractor applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering

AGRIXTRA XL LOAD AND INFLATION VF/SERIES

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)							
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	29 psi	35 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	2 bar	2.4 bar
VF600/70R30	165D	5/10 LT	6880/3120	7990/3625	9115/4135	10250/4650	11365/5155	12490/5665		
		5/10 HT	6370/2890	7410/3360	8455/3835	9500/4310	10540/4780	11585/5255		
		15/25	6435/2920	7485/3395	8545/3875	9590/4350	10635/4825	11695/5305		
		20/30	6370/2890	7410/3360	8455/3835	9500/4310	10540/4780	11585/5255		
		25/40	0/	7265/3295	8290/3760	9315/4225	10330/4685	11355/5150		
		30/50	0/	7265/3295	8290/3760	9315/4225	10330/4685	11355/5150		
		40/65	0/	0/	8290/3760	9315/4225	10330/4685	11355/5150		
VF650/65R34	167D	5/10 LT	7395/3355	8720/3955	9920/4500	11110/5040	12160/5515	13215/5995		
		5/10 HT	6855/3110	8080/3665	9195/4170	10295/4670	11275/5115	12260/5560		
		15/25	6925/3140	8170/3705	9290/4215	10395/4715	11385/5165	12380/5615		
		20/30	6855/3110	8080/3665	9195/4170	10295/4670	11275/5115	12260/5560		
		25/40	0/	7925/3595	9015/4090	10095/4580	11055/5015	12015/5450		
		30/50	0/	7925/3595	9015/4090	10095/4580	11055/5015	12015/5450		
		40/65	0/	0/	9015/4090	10095/4580	11055/5015	12015/5450		
VF710/70R42	179D	5/10 LT	10340/4690	12025/5455	13725/6225	15410/6990	17110/7760	18795/8525		
		5/10 HT	9590/4350	11155/5060	12730/5775	14285/6480	15860/7195	17430/7905		
		15/25	9690/4395	11265/5110	12855/5830	14430/6545	16015/7265	17605/7985		
		20/30	9590/4350	11155/5060	12730/5775	14285/6480	15860/7195	17430/7905		
		25/40	0/	10935/4960	12480/5660	14010/6355	15555/7055	17085/7750		
		30/50	0/	10935/4960	12480/5660	14010/6355	15555/7055	17085/7750		
		40/65	0/	0/	12480/5660	14010/6355	15555/7055	17085/7750		

AGRIXTRA XL LOAD AND INFLATION VF/SERIES

Continued

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)							
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	29 psi	35 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	2 bar	2.4 bar
VF710/75R42	181D	5/10 LT	11010/4995	12810/5810	14615/6630	16400/7440	18210/8260	20005/9075		
		5/10 HT	10205/4630	11870/5385	13545/6145	15210/6900	16885/7660	18550/8415		
		15/25	10305/4675	11995/5440	13680/6205	15365/6970	17055/7735	18740/8500		
		20/30	10205/4630	11870/5385	13545/6145	15210/6900	16885/7660	18550/8415		
		25/40	0/	11640/5280	13285/6025	14915/6765	16555/7510	18190/8250		
		30/50	0/	11640/5280	13285/6025	14915/6765	16555/7510	18190/8250		
		40/65	0/	0/	13285/6025	14915/6765	16555/7510	18190/8250		
VF600/65R28	159D	5/10 LT	5675/2575	6680/3030	7595/3445	8510/3860	9315/4225	10130/4595		
		5/10 HT	5510/2500	6495/2945	7375/3345	8265/3750	9050/4105	9845/4465		
		15/25	5565/2525	6560/2975	7450/3380	8345/3785	9140/4145	9930/4505		
		20/30	5510/2500	6495/2945	7375/3345	8265/3750	9050/4105	9845/4465		
		25/40	5400/2450	6370/2890	7230/3280	8100/3675	8875/4025	9645/4375		
		30/50	5400/2450	6370/2890	7230/3280	8100/3675	8875/4025	9645/4375		
		40/65	5400/2450	6370/2890	7230/3280	8100/3675	8875/4025	9645/4375		



MAXAM AGRIXTRA XL

MS951R - R1W RADIAL DRIVE TIRE

VF/SERIES

Large volume R1W tires for high horsepower tractor applications. Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- ▶ Radial tire construction
- ▶ Self-cleaning tread design
- ▶ Wide tread for maximized performance in the field
- ▶ Low pressure for minimal soil disturbance
- ▶ Premium rubber compounds reduce ozone cracking and weathering



AGRIXTRA XL LOAD AND INFLATION VF/SERIES

Continued

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)							
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	29 psi	35 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	2 bar	2.4 bar
VF650/85R42	180D	5/10 LT	10185/4620	11850/5375	13515/6130	15190/6890	16855/7645	18520/8400		
		5/10 HT	9900/4490	11510/5220	13130/5955	14750/6690	16370/7425	17990/8160		
		15/25	9985/4530	11630/5275	13260/6015	14890/6755	16535/7500	18165/8240		
		20/30	9900/4490	11510/5220	13130/5955	14750/6690	16370/7425	17990/8160		
		25/40	9700/4400	11290/5120	12875/5840	14460/6560	16050/7280	17635/8000		
		30/50	9700/4400	11290/5120	12875/5840	14460/6560	16050/7280	17635/8000		
		40/65	9700/4400	11290/5120	12875/5840	14460/6560	16050/7280	17635/8000		
VF710/60R38	171D	5/10 LT	7825/3550	9115/4135	10395/4715	11675/5295	12950/5875	14240/6460		
		5/10 HT	7605/3450	8850/4015	10095/4580	11345/5145	12590/5710	13835/6275		
		15/25	7685/3485	8940/4055	10195/4625	11455/5195	12710/5765	13965/6335		
		20/30	7605/3450	8850/4015	10095/4580	11345/5145	12590/5710	13835/6275		
		25/40	7465/3385	8675/3935	9900/4490	11120/5045	12335/5595	13560/6150		
		30/50	7465/3385	8675/3935	9900/4490	11120/5045	12335/5595	13560/6150		
		40/65	7465/3385	8675/3935	9900/4490	11120/5045	12335/5595	13560/6150		
VF600/60R30	158D	5/10 LT	5410/2455	6295/2855	7185/3260	8070/3660	8950/4060	9845/4465		
		5/10 HT	5260/2385	6120/2775	6980/3165	7835/3555	8695/3945	9555/4335		
		15/25	5315/2410	6175/2800	7045/3195	7915/3590	8785/3985	9655/4380		
		20/30	5260/2385	6120/2775	6980/3165	7835/3555	8695/3945	9555/4335		
		25/40	5160/2340	5995/2720	6845/3105	7685/3485	8530/3870	9370/4250		
		30/50	5160/2340	5995/2720	6845/3105	7685/3485	8530/3870	9370/4250		
		40/65	5160/2340	5995/2720	6845/3105	7685/3485	8530/3870	9370/4250		

AGRIXTRA XL LOAD AND INFLATION VF/SERIES

Continued

Metric Size	LI / SS	Service Speed (mph/kph)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (lbs/kg)							
			9 psi	12 psi	15 psi	18 psi	20 psi	23 psi	29 psi	35 psi
			0.6 bar	0.8 bar	1 bar	1.2 bar	1.4 bar	1.6 bar	2 bar	2.4 bar
VF710/60R42	173D	5/10 LT	10185/4620	11850/5375	13515/6130	15190/6890	16855/7645	18520/8400		
		5/10 HT	9900/4490	11510/5220	13130/5955	14750/6690	16370/7425	17990/8160		
		15/25	9985/4530	11630/5275	13260/6015	14890/6755	16535/7500	18165/8240		
		20/30	9900/4490	11510/5220	13130/5955	14750/6690	16370/7425	17990/8160		
		25/40	9700/4400	11290/5120	12875/5840	14460/6560	16050/7280	17635/8000		
		30/50	9700/4400	11290/5120	12875/5840	14460/6560	16050/7280	17635/8000		
		40/65	9700/4400	11290/5120	12875/5840	14460/6560	16050/7280	17635/8000		
VF710/65R46	183D	5/10 LT	9975/4525	11675/5295	13370/6065	14860/6740	16345/7415	17615/7990	19740/8955	21220/9625
		5/10 HT	9250/4195	10825/4910	12400/5625	13780/6250	15155/6875	16335/7410	18310/8305	19675/8925
		15/25	9350/4240	10935/4960	12520/5680	13910/6310	15300/6940	16500/7485	18485/8385	19875/9015
		20/30	9250/4195	10825/4910	12400/5625	13780/6250	15155/6875	16335/7410	18310/8305	19675/8925
		25/40	0/	10615/4815	12160/5515	13505/6125	14860/6740	16015/7265	17945/8140	19290/8750
		30/50	0/	10615/4815	12160/5515	13505/6125	14860/6740	16015/7265	17945/8140	19290/8750
		40/65	0/	0/	12160/5515	13505/6125	14860/6740	16015/7265	17945/8140	19290/8750
VF900/60R42	189D	5/10 LT	16690/7570	19410/8805	22475/10195	25210/11435	28275/12825	30655/13905	34060/15450	
		5/10 HT	11355/5150	13205/5990	15290/6935	17140/7775	19225/8720	20845/9455	23160/10505	
		15/25	11465/5200	13325/6045	15430/7000	17305/7850	19410/8805	21055/9550	23390/10610	
		20/30	11355/5150	13205/5990	15290/6935	17140/7775	19225/8720	20845/9455	23160/10505	
		25/40	11120/5045	12940/5870	14990/6800	16800/7620	18850/8550	20435/9270	22710/10300	
		30/50	11120/5045	12940/5870	14990/6800	16800/7620	18850/8550	20435/9270	22710/10300	
		40/65	11120/5045	12940/5870	14990/6800	16800/7620	18850/8550	20435/9270	22710/10300	