

Heavy-duty E3/L3 lug pattern with extra-deep tread depth, designed for maximum traction even in loose ground conditions. This tire boasts the utmost durability and performance.

- ▶ High traction E3/L3 lug pattern with extra-deep tread depth
- ▶ 2-star casing rating across all 80-series for robust casing
- ▶ High-quality casing allows for excellent retreadability
- ▶ Heat-resistant undertread compound ensuring maximum tread life
- ▶ Scuff bar to protect sidewall from impact damage



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| SIZE | RATING | TYPE | RIM | O.D. | S.W. | T.D. | INFLATION PRESSURE | L.C.C. (lbs/kg) | INFLATION PRESSURE | L.C.C. (lbs/kg) | L.I. |
|----------|--------|------|-----------|----------|----------|-------------|--------------------|-----------------|--------------------|------------------|------------|
| | | | | in mm | in mm | 32nds mm | psi KPa | 5 mph 10 kph | psi KPa | 30 mph 50 kph | |
| 14.00R24 | ★ | TL | 10.00VA | 53.8 | 14.8 | 32 | 80 | 15200 | 69 | 9100 | 175A2/157B |
| | | | | 1367 | 376 | 25 | 550 | 6900 | 470 | 4125 | |
| 15.5R25 | ★★ | TL | 12.00/1.3 | 50.3 | 15.5 | 32 | 94 | 15700 | 76 | 9900 | 176A2/160B |
| | | | | 1278 | 394 | 25 | 650 | 7100 | 525 | 4500 | |
| 17.5R25 | ★★ | TL | 14.00/1.5 | 53.1 | 17.5 | 36 | 94 | 18700 | 76 | 12000 | 182A2/167B |
| | | | | 1349 | 445 | 29 | 650 | 8500 | 525 | 5450 | |
| 20.5R25 | ★★ | TL | 17.00/2.0 | 58.8 | 20.5 | 41 | 94 | 25400 | 76 | 16100 | 193A2/177B |
| | | | | 1494 | 521 | 33 | 650 | 11500 | 525 | 7300 | |
| 23.5R25 | ★★ | TL | 19.50/2.5 | 63.7 | 23.5 | 45 | 94 | 32000 | 76 | 20400 | 201A2/185B |
| | | | | 1618 | 597 | 36 | 650 | 14500 | 525 | 9250 | |
| 26.5R25 | ★★ | TL | 22.00/3.0 | 68.9 | 26.5 | 48 | 94 | 40800 | 76 | 25400 | 209A2/193B |
| | | | | 1750 | 673 | 38 | 650 | 18500 | 525 | 11500 | |
| 29.5R25 | ★★ | TL | 25.00/3.5 | 73.8 | 29.5 | 53 | 94 | 49400 | 76 | 30900 | 216A2/200B |
| | | | | 1875 | 749 | 42 | 650 | 22400 | 525 | 14000 | |

