

For cranes operating in highway and off-the-road applications.

- ▶ F-speed rated (50mph/80kph)
- ▶ Low road noise and reduced vibration for improved operator comfort
- ▶ Excellent stability and handling response at highway speeds
- ▶ Deep tread grooves and traction lug pattern improve wet grip and off-road performance

MAXAM MSV01 PRO

## TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (lbs/kg)	L.I.
				in	in	32nds	psi	50 mph	
				mm	mm	mm	KPaw	80 kph	
14.00R24 (385/95R24)	★★★	TT	10.00 W	53.5	15.1	29	130	13200	170F
				1359	383	23	900	6000	
14.00R25 (385/95R25)	★★★	TL	10.00 W	53.5	14.8	29	130	13200	170F
				1360	375	23	900	6000	
16.00R25 (445/95R25)	★★★	TL	11.25/2.0	58.6	17.5	34	130	14800	174F
				1489	445	27	900	6700	
20.5R25 (525/80R25)	★★★	TL	17.00/2.0	58.3	20.6	40	102	16100	177F
				1482	530	31	700	7300	