

MAXAM Tire is a global leader in specialty agricultural tires, offering exceptional value and performance through innovation.

With cutting-edge R&D and manufacturing, we consistently deliver top-quality products that help farmers maximize their equipment's potential.



SIMPLIFYING THE PROCESS

Our performance-driven agricultural tires offer precision-matched solutions that simplify equipment selection. By ensuring the optimal load index for every application, we help farmers make confident, efficient tire choices.



SUPERIOR VALUE

MAXAM's radial agricultural tires are backed by a comprehensive warranty covering manufacturing defects, field hazards, and stubble damage. With MAXAM, farmers can trust their investment is protected.



PERFORMANCE DESIGN

MAXAM's advanced radial construction, featuring a 45° lug design and optimized tread, ensures consistent traction across diverse soils. By maximizing footprint and reducing slip, these tires help farmers achieve significant fuel savings.

RADIAL AG LIMITED WARRANTY

The below Limited Warranty and Adjustment Policy is a commitment of tire replacement under certain specified conditions as provided below. This warranty policy applies to all MAXAM radial agricultural tires as specified below and does not require the existence of a defect to be considered eligible for an adjustment.

AGRICULTURAL USE*	STUBBLE DAMAGE OR FIELD HAZARD COVERAGE	SCRAPER APPLICATION USE*
Up To Eight Years	With Stubble Prevention Device	With Appropriate Weight And Air Pressure Settings
Year 1 100%*	Year 1 80%	Year 1 80%
Year 2 100%*	Year 2 60%	Year 2 60%
Year 3 80%	Year 3 40%	Year 3 40%
Year 4 70%	Year 4 20%	Year 4 20%
Year 5 60%	Year 5 No Coverage	Year 5 No Coverage
Year 6 50%	Year 6 No Coverage	Year 6 No Coverage
Year 7 30%	Year 7 No Coverage	Year 7 No Coverage
Year 8 20%	Year 8 No Coverage	Year 8 No Coverage

*100% FREE REPLACEMENT

See warranty document for policy details & conditions.

PRODUCT ELIGIBILITY

All MAXAM brand radial agricultural tires manufactured and/or sold after January 1, 2018 and distributed by MAXAM per its identification code and production date. This policy applies to either the original owner, the user of the tires or the original purchaser of the agricultural equipment mounted with the tires. The MAXAM agricultural tires covered by this warranty policy belong to the following family of radial products: FLOTXTRA, AGILXTRA, and ROWXTRA. For complete details on the MAXAM Radial Ag Limited Warranty, please visit our website: www.maxamtire.com or contact us at 1-844-MAXAM-NA.



300 Rosewood Drive, Suite 102,
Danvers, MA 01923 USA

Phone: 844-MAXAM-NA | Fax: 978-560-0624

MAXAMTIRE.COM



PERFORMANCE ALL SEASON LONG



AGRICULTURAL IMPLEMENT TIRES

MAXAMTIRE.COM



AGRICULTURAL IMPLEMENT TIRES

FLOTXTRA

MS961R



- Radial implement I3 Flotation Tire
- Radial steel constructed implement tire designed for high loads and speeds up to 40 mph (65 kph) – load range D
- Optimized for both transportation or forage equipment
- High durability, long tread life and improved lateral stability

METRIC SIZE	LOAD INDEX	TIRE WEIGHT (LBS)	T.D. (32NDS)	GFP (SQ IN)
605/70R20.5	176F	603	23	261
500/60R22.5	161D	258	24	210
560/45R22.5	152D	212	24	193
560/60R22.5	165D	298	24	251
600/50R22.5	167D	286	24	237
710/35R22.5	157D	252	24	221
710/40R22.5	161D	321	24	251
600/55R26.5	165D	353	25	279
650/55R26.5	169D	381	25	315
710/50R26.5	170D	435	25	326
800/45R26.5	174D	481	25	364
600/60R30.5	173D	455	29	325
650/65R30.5	176D	534	29	385
710/50R30.5	173D	497	29	353
750/60R30.5	181D	603	30	448

AGILXTRA

MS962R



- Radial implement I3 Flotation Tire
- Steel-belted construction provides high puncture resistance
- Aggressive tread pattern designed for high traction
- Excellent lateral stability for field work and roading
- Wear and cut resistant tread compound ideal for mixed use applications

METRIC SIZE	LOAD INDEX	TIRE WEIGHT (LBS)	T.D. (32NDS)	GFP (SQ IN)
500/60R22.5	155D	211	28	366
560/45R22.5	155D	194	28	217
560/60R22.5	165D	247	28	294
710/45R22.5	165D	293	29	317
600/55R26.5	165D	311	31	269
650/55R26.5	169D	326	31	313
710/50R26.5	170D	373	31	342
850/50R30.5	182D	601	35	477

VF/SERIES

VF560/60R22.5	167D	265	28	309
VF600/55R26.5	173D	327	31	332

ROWXTRA

MS963R



- Steel-belted Radial Construction: Provides superior load capacity, impact resistance, and deformation resistance.
- Special Cut-Resistant Compound to significantly enhance wear life and cut resistance.
- Adaptive Sidewall Design: Engineered with a highly flexible sidewall structure to withstand constant flexing.
- Ribbed Pattern: Ensures even ground contact, effectively reducing soil compaction while lowering rolling resistance.

METRIC SIZE	LOAD INDEX	TIRE WEIGHT (LBS)	T.D. (32NDS)	GFP (SQ IN)
VF/SERIES				
VF240/80R14	113D	41.4	11	77
VF200/90R15	127D	35.9	11	61.5
VF240/80R15	127D	45.4	11	78
VF280/70R15	134D	53	12	93
VF320/70R15	150D	69.4	12	112
VF340/60R15	135D	63	12	111
VF160/95R16	115D	29.8	12	51
VF200/95R16	117D	39.2	12	67
VF245/70R19.5	145D	75.4	17.6	80.8
VF295/75R22.5	155D	106	18.9	145.2