MAXAM MS934



Designed for use on cut-to-length logging equipment. High-strength, belt-stabilized tire construction provides excellent traction and flotation in severe logging applications.

- Heavy-duty shoulder and sidewall
- Maximum protection from cuts, impacts and punctures
- Extra-wide footprint provides exceptional flotation in muddy and wet ground conditions
- Steel-reinforced undertread
- Cut-resistant compound specifically engineered for forestry service
- Nylon wrapped bead prevents unwinding
- Tread pattern specifically designed to integrate with forestry Over-the-Tire Track (OTT) systems




## TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS

| SIZE | P.R. | TYPE | RIM | O.D. | S.W. | T.D. | INFLATION PRESSURE | L.C.C. (LBS/KG) | | L.I. |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | in | in | 32nds | psi | 5mph | 25mph | |
| | | | | mm | mm | mm | KPa | 10kph | 40kph | |
| 780/50-28.5 | 24 | TL | AG26.00 | 60.2 | 31 | 45 | 87 | 23400 | 18700 | 182A8/190A2 |
| | | | | 1529 | 788 | 36 | 600 | 10600 | 8500 | |